### SAFETY DATA SHEET

# Section 1. Chemical Product & Company Identification

MISCO INDUSTRIAL, LLC 1018 STEARMAN DR. WHITE HOUSE, TN 37188 T: 615-334-1861

**Product Name: TM104 CHAMP** 

**Product Use: HEAVY DUTY CLEANER DEGREASER** 

**Product Code: 1366** 

CHEMTREC: 1-800-262-8200

# Section 2. Hazards Identification

**Physical Hazards:** Not Classified

Health Hazards: Skin corrosion/irritation Category 1

Serious eye damage/irritation Category 1

Environmental Hazards: Hazardous to aquatic environment/acute hazard Category 3

Hazardous to aquatic environment/long-term hazard Category 3

**OSHA Defined Hazards:** Not Established

#### **Label Element:**



**Signal Word: DANGER** 

Hazard Statement: Causes severe skin burns and severe eye damage. Harmful if swallowed. Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention): Do not breathe mist or vapor. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective eyewear/face protection.

Precautionary Statements (Response): If swallowed: Rinse mouth. DO NOT induce vomiting. If on skin: Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Specific treatment: Wash contaminated clothing before re-use.

Precautionary Statements (Storage): Store locked up. Store in original container, in upright position, tightly closed.

Precautionary Statements (Disposal): Follow local/regional/national/international regulations. Hazards Not Otherwise Classified: None known.

Product Code 1366	Safety Data Sheet	Product Name: CHAMP	
-------------------	-------------------	---------------------	--

# Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients:	<u>CAS Number</u>	% by Weight	
Potassium Hydroxide	1310-58-3	5-10	
Sodium Salt of Silicic Acid	1344-09-8	1-5	
Ethylene Glycol Monobutyl Ether	111-76-2	1-5	
Nonylphenol Ethoxylate	9016-45-9	1-5	
Monoethanolamine	141-43-5	7-13	

Due to Trade Secret, the exact percentage of composition has been stated as a range. The exact identities of other ingredients has also been withheld as Trade Secret. However, they do not contribute to the identified hazards of the product and will be divulged to proper authorities in an emergency.

#### Section 4. First Aid Measures

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Skin Contact: Immediately take off all contaminated clothing. Rinse skin with large amounts of water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before re-use.

Inhalation: Move to fresh air. Call a physician if symptoms develop or persist.

Ingestion: Call a physician or poison control center immediately. Rinse mouth with water. DO NOT induce vomiting. If vomiting occurs, keep head below hips so that stomach contents do not enter lungs.

Most Important Symptoms/Effects, Acute & Delayed: Burning pain and severe corrosive skin damage.

Serious eye damage; stinging, tearing, redness, swelling and blurred vision. Permanent eye damage including blindness could occur.

Indication of Immediate Medical Attention & Special Treatment Needed: Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

# Section 5. Fire Fighting Measures

Suitable Extinguishing Media: Water fog. Foam. Dry chemical powder. Carbon dioxide. Do not use water jet as this may spread fire.

Specific Hazards Arising From the Chemical: During fire, gases hazardous to health may be formed. Protective Equipment and Precautions for Firefighters: Self contained breathing apparatus and full protective clothing.

#### Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment & Emergency Procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill. Keep out of low areas. Wear appropriate protective equipment and clothing during clean up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods & Materials for Containment & Cleaning Up: This product is miscible in water. Large spills: stop the flow of material, if this is without risk. Dike the spilled material, where possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small spills: wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spilled material to original container.

Environmental Precautions: Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## Section 7. Handling and Storage

Precautions for Safe Handling: Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid releases to the environment. Observe good industrial hygiene practices.

Conditions for Safe Storage, including any Incompatibilities: Store locked up. Store in original tightly closed container. Store away from incompatible materials (see sec. 10).

# Section 8. Exposure Controls/Personal Protection

Occupational Exposure Guidelines: OSHA: Monoethanolamine, 3ppm TWA, 6ppm STEL, ACGIH: Potassium Hydroxide, 2 mg/m3, TWA 2mg/m3, NIOSH: Exposure limits for sodium salt silicic acid have not been established, but 2 mg/m3 is recommended.OSHA PEL:Ethylene glycol mono butyl ether 20ppm TWA, ACGIH 20 ppm TWA

Appropriate Engineering Controls: Good general ventilation (generally 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. It is recommended that users of this product perform a risk assessment to determine the appropriate PPE.

#### **Individual Protection Measures, Personal Protective Equipment:**

Eye/Face: Wear safety glasses with side shields (or goggles) and a face shield.

Skin/Body: Wear chemical resistant gloves and chemical resistant clothing.

Respiratory: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely ash work clothes and protective equipment to remove contaminants.

## Section 9. Physical & Chemical Properties

**Appearance:** Yellow Liquid

Physical State : Liquid Color: Yellow pH: >12 Odor: Amine

Boiling Point: >212 F Odor Threshold: Not available

Vapor Pressure: Unknown Specific Gravity: 1.08
Melting Point/Freeze Point: Unknown Flash Point: >210 F.

Evaporation Rate: Not available Flammability (solid, gas): Non-flammable
Upper Flammability Limit: Not available
Lower Flammability Limit: Not available

Explosive Properties: Not available

Vapor Density: Not available

Water Solubility: Soluble Auto-Ignition Temperature: Not available

Decomposition Temperature: Not available Viscosity: Not available

Oxidizing Properties: Not available

Other Solubilities: Not available

# Section 10. Stability & Reactivity

Reactivity: Reacts violently with strong acids. May react with oxidizing agents.

**Chemical Stability: Stable under normal conditions.** 

Possibility of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions to Avoid: Do not mix with other chemicals. Avoid contact with incompatible materials.

Incompatibility: Acids, oxidizing agents, halogenated materials. Prolonged contact with alkali sensitive metals or alloys.

**Hazardous Polymerization: Will not occur.** 

Hazardous Decomposition Products: Irritating and/or noxious fumes and gases may be emitted upon decomposition. Oxides of sodium.

## Section 11. Toxicological Information

#### **INFORMATION ON LIKELY ROUTES OF EXPOSURE:**

Inhalation: May cause irritation of the respiratory system. Prolonged inhalation may be harmful.

Ingestion: Causes digestive tract burns.

Skin Contact: Causes severe skin burns.

Eye Contact: Causes serious eye damage.

COMPONENT INFORMATION:

Chemical Name Oral LD50 Dermal LD50 Inhalation LC50

Potassium Hydroxide 273 mg/kg N/A N/A Silicic Acid Sodium Salt N/A N/A N/A

Ethylene Glycol Monobutyl Ether 470mg/kg 99mg/kg 450 ppm (rat)4h

(rat) (rabbit) Irritation eye rabbit 20mg severe

Monoethanolamine 500mg/kg 1100mg/kg 11mg/L 4hr

### INFORMATION ON PHYSICAL, CHEMICAL, TOXICOLOGICAL EFFECTS:

Symptoms: Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

# DELAYED & IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT TERM EXPOSURE & LONG TERM EXPOSURE:

Carcinogenicity: Assessment not possible from current data.

**Respiratory Sensitization: Not available.** 

Skin Sensitization: Not expected to cause skin sensitization.

Germ Cell Mutagenicity: No data available to indicate product is mutagenic or genotoxic.

Reproductive Toxicity: Diethanolamine (present at < .028%) shows reproductive toxicity in lab animals.

Specific Target Organ Toxicity, Single exposure: Not classified Specific Target Organ Toxicity, repeated exposure: Not classified.

**Aspiration Hazard: Not available.** 

**Chronic Effects:** prolonged inhalation may be harmful.

## Section 12. Ecological Information

**Ecotoxicity:** Harmful to aquatic life with long lasting effects.

ChemicalAlgae/Aquatic PlantsFishMicroorganismsCrustaceaPotassium HydroxideN/A80mg/I, 96 hrsN/AN/ASodium Salt Silicic AcidN/A2320ppmN/AN/A

Ethylene Glycol 100mg/L 96hr LC50 2950mg/L N/A EC50 1698-1940:24hr

Monobutyl Ether 96hr.

Nonylphenol ethoxylate - LC50 5mg/L 96hr - -

Monoethanolamine EC50 2.8mg/L 72hr

LC50 349mg/L 96hr N/A

EC50 65mg/L 48hr (water flea)

(pseudokirchneriella subcapitata)(carp)

Persistance & Degradability: No data available.

Bioaccumulation: No data available. Mobility in Soil: No data available.

Other adverse Effects: No other adverse effects expected.

## Section 13. Disposal Considerations

Disposal Instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local/regional/national/international regulations. Hazardous waste Code: Waste code should be assigned by discussion between the user, the producer and the waste disposal company.

Waste from Residues/Unused Products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see Disposal Instructions).

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since empty containers may contain product residue, follow all label warnings even after container is emptied.

# Section 14. Transport Information

Regulatory	UN	Proper Shipping	Classes	PG*	Label
Information	Number	Name			
<b>DOT Classification</b>	UN 1760	Liq. cleaning	8	Ш	8
		compound			
IMDG Class	UN 1760	Liq. Cleaning Compound	8	III	8

NOTE: DOT Classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill Of Lading with your shipment.

PG\*: Packing Group

# Section 15. Regulatory Information

#### **U.S. Federal Regulations:**

SARA 313 toxic chemical notification and release reporting:

**Ethylene Glycol Monobutyl Ether** 

CERCLA

Clean Water Act (CWA) 307: Potassium Hydroxide (cas 1310-58-3)

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 Regulated Toxic Substances: Diethanolamine 111-42-2
All Components of this product are listed or exempt from listing on TSCA Inventory.

United States Inventory (TSCA 8b): Ethylene Glycol Monobutyl Ether

US State Right to Know Regulations: Sodium Hydroxide, Sodium Salt Silicic Acic, Monoethanolamine

#### **State Regulations**

California Prop 65: Diethanolamine, known to the state of California to cause cancer (present at

<.028%)

Acute Health HazardYesChronic Health HazardYesFire HazardNoSudden Release of Pressure HazardNoReactive HazardNo

# Section 16. Other Information

NFPA: 3,0,1 HMIS: 3,0,1

Issue Date: 3/03/2017 Revision Date: N/A Revision Note: N/A

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.

Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

\*Note: Hazard Determination System (HDS) ratings are on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on SDS's under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.